

ACCUREASER TOUCH

Bring Your
Digital Creasing
In-House With Our
Affordable Air Feed
Creasing Machine



- Modular Design allows for Pile Feeder Upgrade.
- 2 Crease Widths Standard.
- 1 Perf and 1 Score Standard.
- 12 Crease Location per Sheet
- Automated Setups for 11 Different Creases.
- Intuitive Touchscreen for easy operation.



Machinery Company

www.countmachinery.com

OLMEDO BADIA S.A DE C.V.

www.olmedobadia.com

info@olmedobadia.com

Tel: (55)5557-0397



ACCUCREASER TOUCH FEATURES

Accucreaser Touch Features:

- Automated Distance Recognition allows for auto setups for Half, Tri-fold, Z-fold, Letter fold, Roll fold, Gate fold, Double Gate, and Double Parallel crease jobs.
- Automatic Perfect Bind set-up.
- Crease, Perforating and Feed modes
- Accurate Rotary Actuated Impact Creasing
- Linear Perf/Score capabilities, including micro perf. Up to 4 at a time.
- Bottom Feed Suction or Deep Pile Air Feed Allows 27" of stock to be loaded.
- Batch and Total Counters
- Sheet Spacing Control [on pile feeder model]
- Ability to add Inline transport for feeding the Countcoat GT UV Coater or other UV Coaters.
- Comes with both standard and wide crease dies.
- 18" wide crease widths.
- Intuitive Touch Screen Control

Warranty

Count warrants each new machine against defective parts and workmanship. One year warranty on electrical and mechanical parts. Excludes consumable items.

Specifications

- Electrical: 115/230 50/60hrz
- Max Sheet size: 18" x 20 " [45cm x 45cm]
- Min Sheet size: 3" x 5" [8cm x 12cm]
- Stock Weights: 16lb. - 16 point
- Net Weight - Countcoat UV Coater: 300 lbs. 350 lbs. Crated.
- Overall dimensions L:44" H:44" W: 32"



Bottom
Air/Suction Feed



Linear Perforating Standard



RAC Compression
Crease Assy



Microlateral for easy skew
adjustments



OLMEDO BADIA S.A DE C.V.
www.olmedobadia.com
info@olmedobadia.com
 Tel: (55)5557-0397

Count Machinery Company
 2128 Auto Park Way
 Escondido, CA 92029
 Phone 760-489-1400
 Fax 760-489-1543
info@countmachinery.com
www.countmachinery.com

Auto setups of all the following:

